



rb anche spoc





DREXEL

SWINGMAST

EMX30

DAVE SINCE

RICHIE'S



landoli.com

Yale

SCHWABER
50

fb RITCHIE BROS.
Auctioneers



FB RITCHIE BROS



FRANCO BROS



100



rb
MCHIE BRO
Chosen



rb   







5140A



AC

by carago



Vehicle is equipped with tires in compliance with ANSI B56.1 Safety and Stability requirements. Any replacement tires must meet the same requirements as the original equipment. Failure to comply with these requirements could result in injury to operator or personnel nearby.







DANGER

WARNING

fb BITCHIE BROS.
Auctioneers



PHOTOCHEMICS





DREXEL

50000

LOW HYD 2 FAST SLOW

FB FITCHIE BROS

DREXEL

WARNING
ALARM MUST BE ARMED
When the alarm is armed, the operator must be seated and the machine must be in neutral. If the alarm is not armed, the machine will not operate.

**EMERGENCY
DISCONNECT**

WARNING
CAUTION: High Pressure Hydraulic Fluid
Under Pressure. Do Not Touch.
Do Not Touch Hydraulic Lines or Connections.
Do Not Touch Hydraulic Hoses or Connections.
Do Not Touch Hydraulic Components.
Do Not Touch Hydraulic Connections.
Do Not Touch Hydraulic Lines or Connections.
Do Not Touch Hydraulic Hoses or Connections.
Do Not Touch Hydraulic Components.
Do Not Touch Hydraulic Connections.

DREXEL



DIRECTIONAL HOOKER SWITCH
FORWARD NEUTRAL REVERSE
JOYSTICK FUNCTION TRIGGER
PULL TRIGGER TO CHANGE MODES
CENTER JOYSTICK TO RETURN







landoll.com

SWING MAST

DREXEL

LANDOLL
SL40AC

10112611

JCB

ARCHIEBROS.



Landoll Corporation

1900 North St. Marysville, KS 66508
(785) 562-5381 www.landoll.com

Model: **SL40AC** Truck UL Type: **E**
 Serial Number: **SL40AC-17058-10203**
 Battery Volts: **48** A/H @ 6 Hr: **1,000** Battery UL Type: **1**
 Min. Battery Wt. (lb/kg): **3,250**
 Max. Battery Wt. (lb/kg): **3,900**
 Truck Wt. w/o Battery (lb/kg): **10,000**
 Max. Unladen Truck Wt. (lb/kg): **13,900**
 Reach (in/cm): **3** Shift (in/cm): **3**
 Back Tilt (Deg): **4** Interlock Type: **1**
 Load Tire Size (in): **20 x 9 x 15** Material: **1**

**Truck Capacity for Evenly Distributed Loads
With Vertical or Rearward Tilted Mast**

Standard Rating Mast S/N: **247609**
 Guided Rating Forks: **247609**
 Attachment: **Int. Fork Positioner**

	Capacity lb/kg	Dim. A in/cm	Dim. B in/cm	Dim. C in/cm
XI	4,000 / 1818	24 / 60.9	24 / 60.9	24 / 60.9
X	3,200 / 1455	24 / 60.9	24 / 60.9	24 / 60.9
IX	3,785 / 1709	24 / 60.9	24 / 60.9	24 / 60.9
X	3,010 / 1365	24 / 60.9	24 / 60.9	24 / 60.9
IFPw/extended Kool 1240 / 1243		24 / 60.9	24 / 60.9	24 / 60.9
	3,400 / 1583	24 / 60.9	24 / 60.9	24 / 60.9
IFPw/extended Kool 1660 / 753		24 / 60.9	24 / 60.9	24 / 60.9
	1,300 / 585	24 / 60.9	24 / 60.9	24 / 60.9

This Truck Meets All The Applicable Mandatory Requirements of
ANSI B56.1 Safety Standards for Powered Industrial Trucks

Manufactured Under One or More of the Following Patents
 USA 3,382,994 3,532,238 3,637,100 4,087,776 4,364,444
 Canadian 873,719 1,167,820 Mexico 156,505



