



RONNIE BROS





rbm1018805





NO RICHIE BROS







DREXEL

FB RITCHIE BROS





DANGER

DANGER









50A

PLATE: 100





SI 50AC





FLORIANE PROS





**WARNING**  
This machine is designed to be used only on a hard, level surface. It is not to be used on uneven, soft, or slippery surfaces. The operator must be trained and certified to operate this machine. Failure to follow these instructions may result in injury or death.

WME RESIST

**FB BITCHIE BROS**  
EQUIPMENT

















FRITZ BROS.





BROS.



DURA-TUFF





1000

2025 3400 10000 1111  
E-C-M AERONAUT

rb RAYCHE BROS.  
EQUIPMENT





 **BITCHIE BROS.**









SAFETY INSTRUCTIONS


WARNING

**DREXEL**



1 DIRECTIONAL ROCKER SWITCH  
FORWARD NEUTRAL REVERSE

JOYSTICK FUNCTION - TRIGGER  
PULL TRIGGER TO CHANGE MODES  
CENTER JOYSTICK TO RETURN





EMERGENCY  
DISCONNECT



LANDOLL

DREXEL



1. DIRECTIONAL ROCKER

FORWARD

NEUTRAL

JOYSTICK FUNCTION





INSPECTION SHEET  
DATE: 10/15/15  
TIME: 10:00 AM  
BY: [Signature]  
[Signature]  
[Signature]

**RITCHIE BROS.**  
Auctioneers





landoll.com

LIEBHERR

SWINGMAST

RT RITCHIEBROS



**BASIC BATTERY CARE**

1. Do not charge in closed, unventilated areas.
2. Charge in well-ventilated area.
3. Do not charge in areas where flammable vapors are present.
4. Do not charge in areas where explosive vapors are present.
5. Do not charge in areas where sparks are produced.
6. Do not charge in areas where open flames are present.
7. Do not charge in areas where hot surfaces are present.
8. Do not charge in areas where high voltage is present.
9. Do not charge in areas where high pressure is present.
10. Do not charge in areas where high temperature is present.
11. Do not charge in areas where high humidity is present.
12. Do not charge in areas where high dust is present.
13. Do not charge in areas where high noise is present.
14. Do not charge in areas where high vibration is present.
15. Do not charge in areas where high speed is present.
16. Do not charge in areas where high acceleration is present.
17. Do not charge in areas where high deceleration is present.
18. Do not charge in areas where high shock is present.
19. Do not charge in areas where high impact is present.
20. Do not charge in areas where high pressure is present.

Warning labels with hazard symbols (exclamation mark, flame, etc.) and text.



SI50AC

RTB RITCHIE BROS.  
LAWL







**Product Information**

Model	Power (kW)	Power (kVA)	Weight (kg)
B75-4	75	100	150

**Technical Specifications**

- Rated Power: 75 kW
- Rated Voltage: 230V AC
- Rated Frequency: 50 Hz
- Rated Current: 325 A
- Rated Power Factor: 0.75
- Rated Efficiency: 0.85
- Rated Speed: 1500 rpm
- Rated Life: 20,000 hours

**Operating Conditions**

- Operating Temperature: 0°C to 40°C
- Storage Temperature: -20°C to 60°C
- Relative Humidity: 5% to 95%
- Altitude: 0 to 1000 m

**Safety Information**

- Read the manual before operating the unit.
- Do not touch the unit when it is running.
- Do not use the unit in a confined space.
- Do not use the unit in a flammable or explosive atmosphere.
- Do not use the unit in a wet or damp environment.
- Do not use the unit in a corrosive atmosphere.

**Warranty**

3 years

C/W B75-4





DREXEL

DREXEL

SWINGMAST



5150AC LAMI JILL

FLORIANEPOS





# DREXEL

## Landoll Corporation

1900 North St. Marysville, KS 66508  
(785) 862-5381 www.landoll.com

Model: **EL50AC** Truck UL Type: **II**  
 Serial Number: **2004P-17058-10228**  
 Battery Volts: **48** A/H @ 6 Hr: **1,000** Battery UL Type: **II**  
 Min. Battery Wt. (lb/kg): **3,250**  
 Max. Battery Wt. (lb/kg): **3,900**  
 Truck Wt. w/o Battery (lb/kg): **11,500**  
 Max. Unladen Truck Wt. (lb/kg): **15,100**  
 Reach (in/cm): **196** Shift (in/cm): **21**  
 Back Tilt (Deg): **4** Interlock Type: **None**  
 Load Tire Size (in): **20 x 9.50** Material: **2ply**

### Truck Capacity for Evenly Distributed Loads With Vertical or Rearward Tilted Mast


Standard Rating Mast S/N: **2004P-17058-10228**  
 Guided Rating Forks: **2004P-17058-10228**  
 Attachment: **2004P-17058-10228**

	Capacity lb/kg	Dim. A in/cm	Dim. B in/cm	Dim. C in/cm
X	5,000 / 2273	24 / 60.9	24 / 60.9	180 / 4.57
X	3,840 / 1745	24 / 60.9	24 / 60.9	200 / 5.08
X	4,700 / 2130	24 / 60.9	24 / 60.9	180 / 4.57
X	3,010 / 1367	24 / 60.9	24 / 60.9	200 / 5.08
X	3,250 / 1475	24 / 60.9	24 / 60.9	180 / 4.57
X	3,380 / 1533	24 / 60.9	24 / 60.9	200 / 5.08
X	1,580 / 715	24 / 60.9	24 / 60.9	180 / 4.57
X	1,580 / 715	24 / 60.9	24 / 60.9	200 / 5.08

This Truck Meets All The Applicable Mandatory Requirements Of  
ANSI B56.1 Safety Standards for Powered Industrial Trucks

Manufactured Under One or More of the Following Patents  
 USA 3,382,994 3,532,238 3,637,100 4,087,776 4,364,444  
 Canadian 873,719 1,167,820 Mexico 156,505





4470.6 hrs |







YELLOW

DREXEL



tb BIRCHIE BROS  
EQUIPMENT



