

















MANUFACTURED BY

EVOBUS GMBH
STUTT GART, GERMANY

GVWR

22 920 KG (50 530 LBS)

DATE

July 2016

GAWR

TIRE

RIM

COLD INFLATION PRESSURE
PSI KPA

FRONT 7 500 KG (16 530 LBS)

315 / 80 R 22.5 'J'

22.5 x 9.00

123 849 SINGLE

REAR 9 072 KG (20 000 LBS)

315 / 80 R 22.5 'J'

22.5 x 9.00

94 649 DUAL

TAG 6 350 KG (14 000 LBS)

315 / 80 R 22.5 'J'

22.5 x 9.00

94 649 SINGLE

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS
IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE

V.I.N.

WKKKA574HZH3010288

TYPE OF VEHICLE

BUS









717
S487TC









362022.1 mi
755.1

km/h
mph

mi 80

































S417TC









rb
BATCHMENS
A Division of



0.19 in
32

ON 0 mm in/F HOLD



Continental



185/65R14
100H



Conti Coach HAB

01/2003
32110113
10001 222511-102011

HAB
10001 222511-102011



315/80 R 22.5

R

22.5

REGROOVABLE
DESIGNED FOR



REGROOVABLE



M+S



BOTO

315/80R22-5

STANDARD TRUCK

1000000

BTR



ON

0

mm

in/F

HOLD

0.0 in
0.0



0 $\frac{16}{32}$ in

mm in/F

HOLD

A close-up photograph of a tire's sidewall and tread. The tire is mounted on a silver-colored metal rim. The word "BOTO" is embossed in a large, bold, sans-serif font on the sidewall. The tread pattern is visible at the top of the frame, showing several longitudinal grooves. The metal rim has several circular holes. The overall appearance is that of a well-used, possibly off-road or heavy-duty tire.

BOTO

BT 9058

DOT 800J BIFL 2519

001310

315/80R22.5

STANDARD RIM 900



ON 0 mm in/F HOLD

0.12 in
3.2 mm

KAPSEN

WANG ET CRIMA

A close-up photograph of a tire tread. The tire is dark grey or black and features a pattern of longitudinal grooves. The text "HS107" is embossed in a large, bold, sans-serif font across the center of the tread. To the right of "HS107", the letters "S" and "R" are partially visible, suggesting the word "SERRA". The top edge of the tire shows a series of small, vertical sipes. The background is a light-colored, gravelly surface.

HS107

315/30R22.5
RESURFACIBLE
STANDARD RIMS 115



BECKMAN
TOOL

ON 0 mm in/F HOLD

1.7
in



BOTO



BT 968

315/80R22.5

STANDARD



ON

0

mm

in/F

HOLD

0.00 in



0.19
32

0 mm in/F HOLD

0.19
32

A close-up photograph of a Continental tire mounted on a silver metal rim. The tire is dark grey and shows some wear. The word "Continental" is embossed in a large, serif font on the sidewall of the tire. The rim has several circular holes. The background is a light-colored gravel surface.

Continental





A 315/80 R 22

© 1995































Engine

T Read version information

B Component ID: DTDSC*47IN13*C0243306

* *

VIN Code: WKKA574H2H3010286

Software ID: 036*000*000*000*R**A*011

*004*15*06*29*09*20*16.8200.00117*

Total Vehicle Distance(miles): 360059.21

DIESELHANDHELD



Diagnose Process

System Information

e Information

No DTCs

OK