



















Mfd by VAN HOOL N.V. Lier 2500 BELGIUM

Month / Year of construction: 01/15

GVWR: 54.000 Lb

	GAWR	TIRE SIZE LOAD RANGE	RIM SIZE	COLD INFLATION PRESSURE
Front	17.640 Lb	315/80R22,5 - L	9,00x22,5	125 Psi (Single)
First intermediate	27.575 Lb	315/80R22,5 - L	9,00x22,5	110 Psi (Dual)
Rear	17.640 Lb	315/80R22,5 - L	9,00x22,5	125 Psi (Single)

This vehicle conforms to all applicable U.S. Federal Motor Vehicle Safety Standards in effect on the date of manufacture shown above.

GVWR and GAWR are based on ORIGINAL equipment. Any change may affect vehicle capacities. See Owner's Manual for other tire and capacity information.

Vehicle identification number : -YE2XC21B4F3048566-
Classification : BUS

PRODUCTION NUMBER

N°

48566




















Connection Failed

Connection Failed




Option 1 - Verify the adapter has power and is reading vehicle data. Use the [DLA+ Connectivity Tool](#) for verification.



Option 2 - Unplug adapter from USB and vehicle diagnostics port and reattach to the computer and vehicle.

Option 3 - Close all open diagnostics programs and try again.



Option 4 - Close all open programs, restart computer and restart the application.

Navigation Support Information - Connection Failed: RPT1210 Error 142

Type here to search



2:18 PM 8/21/2019

DELL





Wi-Fi is available on all routes. Please use responsibly.

BICYCLE RACKS
Two bicycle racks are located at the front of the bus. Bicycles must be secured properly and not exceed 6'6" in height.

COVID-19 SAFETY
Please wear your seat belt and follow all safety instructions. For more information, visit www.washstate.edu/covid19.

QR CODE

Wi-Fi is available on all routes. Please use responsibly.

BICYCLE RACKS
Two bicycle racks are located at the front of the bus. Bicycles must be secured properly and not exceed 6'6" in height.

COVID-19 SAFETY
Please wear your seat belt and follow all safety instructions. For more information, visit www.washstate.edu/covid19.

QR CODE


For more details, visit www.washstate.edu/covid19.











CUSTOMER SERVICE

AUSTRALIA: 1-800-023-226
EUROPE/MIDDLE EAST/AFRICA:

USA / CANADA: 1-800-445-1980

MEXICO: 01-800-902-7100



DETROIT

IMPORTANT ENGINE INFORMATION

FUEL RATE AT ADV. HP: 282.4 MM³/STROKE

INITIAL INJECTION TIMING: 17.0 DEG BTC

ENGINE FAMILY: EDDXH12.8FED

UNIT: 47193450283043

DISP: 12.8 LITERS

ADV HP: 500 @ 1800 RPM MODEL: DD13

MFG. DATE: SEP 2014 MIN IDLE: 600 RPM

VALVE LASH: EXHAUST 0.6 MM INTAKE 0.4 MM

"DELEGATED ASSEMBLY" "ESS EXEMPT"

EMISSION CONTROL SYSTEMS: DOI, TC, CAC,

ECM, EGR, OC, PTOX, SCR-U, AIOX

"FOR USE IN VOCATIONAL OR TRACTOR
VEHICLES"

THIS ENGINE CONFORMS TO U.S. EPA AND
CALIFORNIA REGULATIONS APPLICABLE TO
2014 MODEL YEAR NEW HEAVY DUTY DIESEL
CYCLE ENGINES. THIS ENGINE HAS A PRIMARY
SERVICE APPLICATION AS A HEAVY HEAVY DUTY
ENGINE. THIS ENGINE IS NOT CERTIFIED FOR
USE IN AN URBAN BUS AS DEFINED AT
40 CFR 86.093-2. SALE OF THIS ENGINE FOR
USE IN AN URBAN BUS IS A VIOLATION OF
FEDERAL LAW UNDER THE CLEAN AIR ACT. THIS
ENGINE IS CERTIFIED TO OPERATE ON ULTRA
LOW SULFUR DIESEL FUEL.



